

## **NYX HYPER-4** Hybrid 4CH TVI/AHD + 1CH IP DVR/NVR

## **Features**

The NYX HYPER-4 is an 4 channel High Definition Hybrid DVR/NVR, supporting TVI, AHD, WD1, D1 and IP camera formats.

Adopting the most advanced SOC technology to ensure high definition recording in each channel and outstanding reliability of the system.

Full 1080P high definition display output. Intuitive and user-friendly Graphical User Interface (GUI). QR code support for easy remote networking configuration.



## **Specifications**

System	Compression	H.264
	os	Embedded Linux
	Performance	Pentaplex: preview, record, playback, backup and remote access
Video	Input	4 Channel BNC
		1080P @ 30/25fps, 720P @ 30/25fps, WD1, D1
	IP Input / Bandwidth	IP Camera x 1 / 6Mbps
	Output HDMI/VGA	1080P @ 30/25fps
	Spot Monitor Output	BNC x1 (CVBS)
Audio	Input	RCA x 4
	Output	RCA x 1
	2-way audio	Yes
Record	Resolution	1080P, 720P
	Frame Rate NTSC	1080P @ 120fps
	Frame Rate PAL	1080P @ 100fps
	Bitrate	768Kbps ~ 8Mbps VBR / CBR
	Mode	Manual, timer, motion, sensor
IP Input	Resolution/Frame Rate	1080P @ 21fps
Playback	Playback	Up to 4CH analog simultaneous / 1CH IP
	Search	Time / Calendar / Event (motion)
	Function	Play, pause, FF, FB, digital zoom
	Mode	Motion, Video Loss
Alarm	Input	4
	Output	1
	Triggering	Record, PTZ preset, email
Network	Interface	RJ45 x1 : 10/100 Mbps
	Protocol	TCP/IP, UDP, DHCP, DNS, DDNS, NTP, SMTP, PPPoE
	Remote Access	Max 10 users online, dual stream
Smartphone	Platform	iOS, Android
Storage	HDD	SATA x1 Max 6TB per HDD
Backup	Backup	USB Flashdrive, USB mobile HDD, Network
Ports	USB	USB 2.0 x1 (front panel), USB 2.0 x1 (rear panel)
Other	Remote Controller	Yes
	Power Consumption	≤ 5W (without HDD) 12V DC
	Dimensions (mm)	255(W) x 210(D) x 42(H)
	Working Environment	-10°C ~ 50°C 10% ~ 90% humidity



network viewing

TVI, AHD, WDI, D1























1<sub>Ch</sub>

