

# NYX

# NYX IP View KP+

## 2MP KP Video Intercom

### Features

- 2MP (1920×1080) H.265 full real-time encoding
- Visual intercom function to Superlive + App
- Access control function by swiping card or using app
- Face recognition with liveness test
- ICR auto switch, true day / night
- White light for night view + IR
- Built-in microphone & speaker for 2-way audio
- Can be used as an extra camera for NYX cctv system
- 2.4GHz 802.11b/g/n Wi-Fi connectivity
- SD Card Recording up to 256GB
- PoE or 12VDC powered
- Supports iPhone, iPad, Android remote monitoring



### Specifications

Image Sensor	1/2.8" Progressive Scan CMOS
Resolution	2MP(1920x1080), 720P, D1, CIF
Min. Illumination	0 lux with white light on 0.0085lux Colour
Lens	2.3mm @F2.2, Angle of View 139°, Vertical FOV:74°
Day & Night	ICR Filter
Video Format	H.265 / H.264 / MJPEG
Main Stream	60Hz: 1080P/720P(1~30fps) 50Hz: 1080P/720P(1~25fps)
Wide Dynamic	Digital WDR 80dB
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, Noise Reduction
2-way Audio	Internal microphone, Internal speaker
Alarm Interface	alarm input, 2x door lock output, 2x Rex input, Wiegand
Smart Alarm	Face Recognition
IR Distance	Up to 1m
Card Type	Mifare card /Desfire /FM1208 Card/Gicard 13.56 MHz
SD Card Recording	Motion triggered recording. Up to 256 GB capacity
Remote Access	Edge Browser, CMS Software up to 4 users
Network Protocols	IPV4, IPV6, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, WPS, SSL, TLS, FTP, SNMP, 802.1x, UPnP, HTTPs, QoS
Wi-Fi Band	2.4GHz 802.11b/g/n
Wi-Fi Range	Up to 50M
Wi-Fi Security	WEP, WPA-PSK, WPA2-PSK
Power Supply	DC12V / 48V PoE
Power Usage	6W with light on
Operating Env.	-20°~ 60°C, <95% Humidity (non-condensing)
Housing Material	Plastic body and metal base
Dimensions	210mm x 104mm x 30mm
Weight	600g

Product specifications and appearance subject to change without notice

## 2.4 GHz



### Access Control

Card reader, **Wiegand** interface and door strike output makes access control implementation **quick & easy**



### Facial Recognition

Dual camera with Liveness Test to make sure the face is detected with super reliability. Can be used to open doors and send alerts.Face database,



## 256GB SD Card Recording

