# IPB4-28F IQ+ Wifi

Οηνις S



#### **Features**

- 4MP (2592x1520) H.265 full real-time encoding
- 2.4GHz 802.11b/g/n Wi-Fi connectivity
- Al Intelligence Analytics smart triggering
- People & Vehicle Detection
- ICR auto switch, true day / night Up to 30m IR night view distance
- Built-in microphone
- Triple Stream
- 3D DNR, digital WDR
- SD Card Recording up to 128GB PoE or 12VDC powered for Wifi
- Supports iPhone, iPad, Android remote monitoring





# **People & Vehicle Detection**

The IQ+ camera series incorporates advanced AI features that can detect and classify people and vehicles, allowing you to quickly search footage or be alerted via Push Notifications





### Specifications

Image Sensor	1/3" CMOS
Resolution	4MP(2592x1520), 720P, D1, CIF
Min. Illumination	0.005 lux @F1.4, AGC on; 0 lux with IR
Lens	2.8mm @F1.6, Angle of View 100°
Day & Night	ICR Filter
Video Format	H.265 / H.264 / MJPEG
Main Stream	60Hz: 4MP,1080P/720P(1~30fps)
	50Hz: 4MP,1080P/720P(1~25fps)
Wide Dynamic	Digital WDR 120dB
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast,
	Wide Dynamic, Sharpen, Noise Reduction
2-way Audio	Internal microphone
Alarm Interface	1x alarm input, 1x dry contact relay output
Smart Alarm	PIR detector, Intrusion, Tripwire, Motion Alarm
IR Distance	Up to 10m
PIR Range	7m - Horizontal angle 100°
SD Card Recording	Motion triggered recording. Up to 128GB capacity
Remote Access	Browser, CMS Software up to 4 simultaneous users
Network Protocols	IPv4, IPv6, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, WPS, SSL, TLS, FTP, SNMP, 802.1x, UPnP, HTTPs, QoS
Wi-Fi Band	2.4GHz 802.11b/g/n
Wi-Fi Range	Up to 50M
Wi-Fi Security	WEP, WPA-PSK, WPA2-PSK
Power Supply	DC12V / 48V PoE
Power Usage	<4.5W with IR on
Operating Env.	-30°~ 60°C, <95% Humidity (non-condensing)
Housing Material	Metal body and base
Dimensions	170mm x 80mm x 80mm
Weight	500g
	Product enceifications and appearance subject to change without notice

Product specifications and appearance subject to change without notice

## **Mounting Accessories**



JB-PM



