



Features

- 6MP (3078×2048) H.265+ full real-time encoding
- Low-noise STARLIGHT sensor
- People & Vehicle Detection
- IP67 ingress protection
- Intelligence Analytics smart triggering
- ICR auto switch, true day / night
- 30~50m IR night view distance
- 3D DNR, true WDR
- Triple Stream
- PoE power or 12V DC
- Supports iPhone, iPad, Android remote monitoring



People & Vehicle Detection

The IQ+ camera series incorporates advanced AI features that can detect and classify people and vehicles, allowing you to quickly search footage or be alerted via Push Notifications



256_{GB} SD Card Recording



Intelligence Analytics

Get **FAST** search results by configuring in-built image analytic algorithms.

Supports Tripwire, Region Entry & Exit, Intrusion & Video Exception



Specifications

| Image Sensor | 1/ 2.7" CMOS |
|------------------------|---|
| Resolution | 6MP(3078×2048), 2K, 3M, 2M, 720P, D1, CIF |
| Min. Illumination | 0.007lux @F1.6, AGC on; 0 lux with IR |
| Lens | 2.8mm @F1.6, Angle of View 100° |
| Day & Night | ICR Filter |
| Video Format | H.265+ / H.265 / H.264+ / H264 / MJPEG |
| Main Stream | 60Hz: 6MP(1~20fps), 50Hz: 4MP(1~25fps) |
| Wide Dynamic | True WDR 120dB |
| Image Settings | ROI, Saturation, Brightness, Chroma, Contrast, |
| | Wide Dynamic, Sharpen, Noise Reduction |
| Audio | Mic input x1 |
| Intelligence Analytics | Tripwire, Entry/Exit, Target Detection, Video Exception |
| Smart Alarm | Face Detection, Intelligence Analytics, Motion Alarm |
| IR Distance | 30~50m |
| Smart IR | Switchable |
| SD Card Capacity | 256 GB |
| Remote | IE Browser, Edge, Chrome, CMS Software up to 4 users |
| Protocol | TCP/IP,UDP,DHCP,NTP,RTSP,PPPoE,DDNS,SMTP,FTP |
| Housing Rating | IP67 |
| Power Supply | DC 12V / 48V PoE |
| Power Usage | <9W with IR on |
| Operating Env. | -30°~ 60°C, <95% Humidity (non-condensing) |
| Housing Material | Metal body and base |
| Dimensions | 218 x 80 x 80mm |
| Weight | 670g |

Product specifications and appearance subject to change without notice

Mounting Accessories

JB-301

JB-PM



