





- 8MP (3840×2160) H.265+ full real-time encoding
- Low-noise LOW LIGHT sensor
- People & Vehicle Detection
- Static facial recognition capability
- Intelligence Analytics smart triggering
- ICR auto switch, true day / night
- 20~30m IR night view distance
- 3D DNR, true WDR
- · Built-in microphone
- Triple Stream
- PoE power or 12V DC
- Supports iPhone, iPad, Android remote monitoring
- IP67 ingress protection



People & Vehicle Detection

The IQ+ camera series incorporates advanced AI features that can detect and classify people and vehicles, allowing you to quickly search footage or be alerted via Push Notifications



IQ Face Recognition

Cutting-edge Facial Analytics Engine detects the presence of a person's face facilitating quick searches and notifications with NYX IQ series recorders



Intelligence Analytics

Get **FAST** search results by configuring in-built image analytic algorithms.

Supports Tripwire, Region Entry & Exit, Target Counting, Intrusion & Video Exception



128_{GB} SD Card Recording



Specifications



Image Sensor	1/3" CMOS
Resolution	8MP(3840×2160), 2K, 3M, 2M, 720P, D1, CIF
Min. Illumination	0.02 lux @F1.6, AGC on; 0 lux with IR
Lens	2.8mm @F1.6, Angle of View 109°
Day & Night	ICR Filter
Video Format	H.265+ / H.265 / H.264+ / H264 / MJPEG
Main Stream	60Hz: 4MP(1~30fps), 50Hz: 4MP(1~25fps)
Wide Dynamic	True WDR 120dB
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast,
	Wide Dynamic, Sharpen, Noise Reduction
Audio	Internal Mic x1, Mic input x1
Intelligence Analytics	Tripwire, Entry/Exit, Target Counting, Intrusion, Exception
Smart Alarm	Face Detection, Intelligence Analytics, Motion Alarm
IR Distance	20~30m
Smart IR	Switchable
SD Card Capacity	128GB
Remote	IE Browser, CMS Software up to 4 simultaneous users
Protocol	TCP/IP,UDP,DHCP,NTP,RTSP,PPPoE,DDNS,SMTP,FTP
Housing Rating	IP67
Power Supply	DC 12V / 48V PoE
Power Usage	<7.5W with IR on
Operating Env.	-30°~ 60°C, <95% Humidity (non-condensing)
Dimensions	Ø109 x 98mm (H)
Weight	460g
Paradication of the state and an arrangement of the state	

Product specifications and appearance subject to change without notice

Mounting Accessories

WM-EB

JB-EB

JB-302

LEDGE 1