

# NYX

IPF-4

## 4MP Full Body

### Features

- 4MP (2592x1520) H.265 full real time encoding
- C / CS Lens mount
- Intelligence Analytics smart triggering
- ICR auto switch, true day / night
- 3D DNR, digital WDR
- ROI encoding
- Triple Stream
- SD Card Edge recording
- Alarm input & output
- Supports CVBS video output and 2-way audio
- Supports DC12V / AC24V / PoE power supply
- Supports smart phone, iPad, remote monitoring



### Intelligence Analytics

Get **FAST** search results by configuring in-built **image analytic algorithms**.

Supports Tripwire, Abandoned Object, Missing Object, Video Exception & Intrusion



### H.265 HEVC

More **efficient** video encoding allows for **longer** recording time without sacrificing image **quality**

### 128GB SD Card Recording



### Specifications



Image Sensor	1/3" CMOS
Resolution	4MP(2592x1520), 3MP (2560x1440), 2MP(1920x1080), 720P(1280x720), D1, CIF
Min. Illumination	0.05 lux @F1.2, AGC on
Lens Mount	C / CS
Day & Night	ICR Filter
Video Format	H.265 / H.264 / MJPEG
Main Stream	60Hz: 4MP / 3MP / 1080P / 720P - (1~30fps) 50Hz: 4MP / 3MP / 1080P / 720P - (1~25fps)
Bit Rate	64kbps ~ 10Mbps
Wide Dynamic	Digital WDR 120dB
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, Noise Reduction
Audio	Mic input x1, Line out x1
Video Out	CVBS
Smart Alarm	Motion Alarm, Sensor Alarm, Intelligence Analytics
Alarm	1x Input / 1x Output
Remote	IE Browser, CMS Software up to 10 simultaneous users
Protocol	TCP/IP,UDP,DHCP,NTP,RTSP,PPPoE,DDNS,SMTp,FTP
Serial Connection	RS485
Storage	SD card local storage (128GB), network remote storage
Power Supply	DC 12V / AC24V / PoE
Power Usage	<2.5W
Operating Env.	-20°~ 50°C, 10%~90% Humidity
Dimensions	70mm x 60mm x 145mm
Weight	400g

Product specifications and appearance subject to change without notice



AWB

Sync

AGC

PoE



www.cctvsupplies.com.au

2/175 Currumburra Road  
Ashmore, Qld 4212  
(07) 5527 9949