

# NYX

## NYX Multi Station

## NYX Multi Station



### Features

- 7 inch IPS touch screen
- A maximum of 6 indoor stations in the same room
- Supports live preview of door stations and NVR cameras
- Supports snapshot when calling via door station (micro SD)
- Supports "Do Not Disturb" function
- Supports noise suppression and echo cancellation
- 8CH zone alarm access function
- Self-define unlocking password
- Supports 2.4G WIFI
- Supports 1CH 12V 200mA power o/p for powering a sensor

2.4GHz 

48V POE Cat 5e / 6 or 12V/Wifi Connection

### Multiple Room Stations

1 x Master Multi Station and 5 Subs for use with NYX IP View + & View KP+

### CCTV Camera Monitoring

Can display up to 4 CCTV cameras when connected to a NYX CCTV System

256GB  
SD Card  
Recording



### Specifications

Operating System	Linux
Display Screen	7 inch IPS touch screen
Display Resolution	1024 600, brightness:300 cd/m2
Operation Method	Capacitive touch screen
Video Input	Max. 4CH videos can be viewed simultaneously
Network Input Resolution	6MP/5MP/4MP/3MP/1080P/12801024/960P/720P
Compression	H.265+/H.265/ H.264 / MJPEG
Local Input	Built-in microphone
Local Output	Built-in speaker
Compression	G.711(U/A)
Resolution	Up to 2MP
Frame Rate	NTSC: 30fps; PAL:25fps
Simultaneous Playback	Max.1CH
Linked IPC	Max. 16 CH
Linked Indoor Extensions	Max. 5
Interface	RJ 45 100 Mbps self-adaptive Ethernet port 1
Wireless Network	WiFi 802.11b/g/n
Protocol	TCP / IP, DHCP, DNS, NTP, etc.
Incoming/Outgoing B/W	40/40Mbps
Audio	Built-in speaker and mic, noise and echo suppression
Storage	Built-in micro SD card slot, up to 256GB
Alarm Input	8CH
Wi-Fi	Yes,2.4G Wi-Fi
Power Output	DC12V 200mA (if DC12V power supply is used)
Power	DC12V/POE
Power Consumption	< 6W
Dimensions(mm)	180.6 135.6 26.8
Weight (net)	Approx.0.36kg
Installation	Wall mounting

Product specifications and appearance subject to change without notice