

MYX

D6VFL Ultimate

Ultimate

Features

- 6MP (3200×1800) H.265+ full real-time encoding
- Voice Annunciation/Siren and Two way Speech
- AI People & Vehicle Detection
- Red & Blue LED Warning Lights
- White Sensor Light or Colour at Night
- Intelligence Analytics smart triggering
- 30~40m IR night view distance
- Triple Stream, 3D DNR, digital WDR
- PoE power or 12V DC
- 2.8~12mm Motorized VF Auto-Focus Lens
- IP67 ingress protection



Two Way Speech



Audible Alert



Light Alert



Sensor Light



Colour At Night



Audible Perimeter Alert

When triggered, the camera can announce pre-recorded messages or siren. Automatically switches to 2-way audio mode.

Visual Perimeter Alert

Red and Blue Flashing LEDs to ward off intruders. Can be set to sensor light mode or white light mode to give colour at night.

AI People & Vehicle Detection

This advanced AI feature can detect people, vehicles and faces allowing you to quickly search footage or be alerted via Push Notifications.



5 Cameras In One

- Two Way Speech
- Audible Alerts
- Flashing Red and Blue Led Alerts
- AI Triggered White Sensor Light
- White Light for Colour at Night

256GB
SD Card
Recording



Specifications

Image Sensor	1 / 2.39" CMOS
Resolution	6MP (3200×1800), 2K, 3MP, 1080P, 720P, D1, CIF
Min. Illumination	0.02 lux @F1.6, AGC on; 0 lux with IR, White light
Lens	2.8~12mm Motorized Vari-focal @F1.4, AoV 10°~46°
Day & Night	ICR Filter
Video Format	H.265+ / H.265 / H.264+ / H264 / MJPEG
Main Stream	60Hz: 8MP(1~30fps), 50Hz: 8MP(1~25fps)
Wide Dynamic	Digital WDR
Image Settings	ROI, Hue, Saturation, Brightness, Contrast, BLC, HWDR, Sharpen, Noise Reduction, Distortion Correction
Audio	Internal Mic x1, External Mic input x1, Internal Speaker, Audio output x1
Alarm interface	
Intelligence Analytics	Tripwire, Entry/Exit, Target Counting, Intrusion, Exception
Smart Alarm	Intelligence Analytics(people & vehicle), Motion
Illumination	30~40m IR distance, 30~40m White distance
Smart IR	Switchable
SD Card Recording	Motion triggered recording. Up to 256GB capacity
Remote	Edge Browser, CMS Software up to 4 simultaneous users
Protocol	TCP/IP,UDP,DHCP,NTP,RTSP,PPPoE,DDNS,SMTP,FTP
Housing Rating	IP66
Power Supply	DC 12V / 48V PoE
Power Usage	<12.5W with IR on
Operating Env.	-30°~ 60°C, <95% Humidity (non-condensing)
Dimensions	Ø 130mm x 110(H)
Weight	0.64kg



Product specifications and appearance subject to change without notice

Mounting Accessories

JB-303

Ledge 2

