

# NYX

NYX VT432 THERMAL

THERMAL / OPTICAL AI

STARLIGHT

## Features

- Dual image fusion (thermal image and optical image)
- Thermal Resolution: 256×192 12μm
- Temperature range: -20°C~150°C
- Multi-palette: white hot, black hot, iron oxide, etc.
- Optical 4MP (2592×1520) H.265+ 2.8 Lens
- People & Vehicle Detection
- Intelligence Analytics smart triggering
- ICR auto switch, true day/night
- 30~50m IR night view distance
- Built-in microphone
- 3D DNR, digital WDR, Triple Stream
- PoE or 12VDC power supply
- Supports iPhone, iPad, Android
- IP67 ingress protection



AUTOFOCUS ONVIF S

## People & Vehicle Detection

The IQ+ camera series incorporates advanced AI features that can detect and classify people and vehicles, allowing you to quickly search footage or be alerted via Push Notifications



## IQ Face Recognition

Cutting-edge Facial Analytics Engine detects the presence of a person's face facilitating quick searches and notifications with NYX IQ series recorders



## Intelligence Analytics

Get FAST search results by configuring in-built image analytic algorithms. Supports Tripwire, Region Entry & Exit, Target Counting, Intrusion & Video Exception



256GB SD Card Recording



## Specifications

Thermal Resolution	256 x 192 12μm NETD: 50mK(@25 C, F#=1.0
Optical Resolution	1/ 2.7" CMOS 4MP(2592×1944), 2MP, 720P, D1, CIF
Min. Illumination	0.02 lux @F1.4, AGC on; 0 lux with IR
Lens	4mm @F1.4, AoV 81° Thermal 3.2mm@ F1.1
Day & Night	ICR Filter
Video Format	H.265+ / H.265 / H264+ / H.264 / MJPEG
Main Stream	60Hz: 4MP/2K/3MP/2MP/720P(1~30fps) 50Hz: 4MP/2K/3MP/2MP/720P(1~25fps)
Wide Dynamic	True WDR 120dB
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, Noise Reduction
Audio	Internal Mic x1
Intelligence Analytics	Tripwire, Entry/Exit, Target Counting, Intrusion, Exception
Smart Alarm	Face Recognition, Intelligence Analytics, Motion Alarm
IR Distance	30~50m
Smart IR	Switchable
SD Card Capacity	256GB
Remote	IE Browser, CMS Software up to 10 simultaneous users
Protocol	TCP/IP,UDP,DHCP,NTP,RTSP,PPPoE,DDNS,SMTP,FTP
Housing Rating	IP67
Power Supply	DC 12V / 48V PoE
Power Usage	<9.5W with IR on
Operating Env.	-30°~ 60°C, <95% Humidity (non-condensing)
Dimensions	Ø 130mm x (H)110mm
Weight	800g

Product specifications and appearance subject to change without notice

## Mounting Accessories

