

NYX

IPB5-28F

5MP PoE IP Bullet

Features

- 5MP (2592x1944) H.265 full real time encoding
- Intelligence Analytics smart triggering
- ICR auto switch, true day / night
- 20 ~ 30m IR night view distance
- 3D DNR, digital WDR
- ROI encoding
- Support CVBS video output and one-way audio
- Support PoE power supply
- Support smart phone, iPad, remote monitoring
- IP66 ingress protection
- Triple Stream



ONVIF

Specifications

Image Sensor	1/1.8" CMOS
Resolution	5MP(2592x1944), 4MP, 3MP, 2MP, 720P, D1, CIF
Min. Illumination	0.05 lux @F1.2, AGC on; 0 lux with IR
Lens	2.8mm @F1.6, Angle of View 105°
Day & Night	ICR Filter
Video Format	H.265 / H.264 / MJPEG
Main Stream	60Hz: 5MP/4MP/3MP/2MP/720P(1~30fps) 50Hz: 5MP/4MP/3MP/2MP/720P(1~25fps)
Wide Dynamic	Digital WDR
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, Noise Reduction
Video Analytics	Intrusion, Missing/Abandoned Object, Trip-wire
Audio	Mic input x1
Video Out	CVBS
Smart Alarm	Motion Alarm, Intelligence Analytics
IR Distance	20~30m
Remote	IE Browser, CMS Software up to 10 simultaneous users
Protocol	TCP/IP,UDP,DHCP,NTP,RTSP,PPPoE,DDNS,SMTP,FTP
Housing Rating	IP66
Power Supply	DC 12V / PoE
Power Usage	<2.5W (<6W with IR on)
Operating Env.	-20°~ 50°C, 10%~90% Humidity
Dimensions	Ø 87 x 219mm
Weight	609g

Product specifications and appearance subject to change without notice

Intelligence Analytics

Get **FAST** search results by configuring in-built **image analytic algorithms**.

Supports Tripwire, Abandoned Object, Missing Object, Video Exception & Intrusion



H.265 HEVC

More **efficient** video encoding allows for **longer** recording time without sacrificing **image quality**



4MP Sensor



0 Lux Min. Illumination



Digital WDR



Motion Detection



True Day&Night



AWB



Sync



AGC



PoE





IP66 Rating

Mounting Accessories

JB-EB

JB-PM



www.cctvsupplies.com.au

2/175 Currumburra Road
Ashmore, Qld 4212
(07) 5527 9949