

# MYX STARLIGHT series

## Features

The new **STARLIGHT** series enhances night vision and greatly reduces image noise ensuring sharp video at night.

- 2MP (1920×1080) H.265 @ 25/30fps
- ICR auto switch, true day / night
- 20~30m IR night view distance
- 3D DNR, digital WDR
- SD Card Recording up to 128GB
- Triple Stream
- ROI encoding
- Support PoE power supply
- Support smart phone, iPad, remote monitoring
- IP67 ingress protection



**ENHANCED  
LOW NOISE  
NIGHT VISION**

## Specifications



Image Sensor	1/2.7" CMOS
Resolution	2MP(1920x1080), 720P(1280x720), D1, CIF
Min. Illumination	0.01 lux @F1.2, AGC on; 0 lux with IR
Lens	2.8mm @F1.6, Angle of View 100°
Day & Night	ICR Filter
Video Format	H.265 / H.264 / MJPEG
Main Stream	60Hz: 1080P(1~30fps) / 720P(1~30fps) 50Hz: 1080P(1~25fps) / 720P(1~25fps)
Wide Dynamic	Digital WDR
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, Noise Reduction
Smart Alarm	Motion Alarm
IR Distance	20~30m
SD Card Capacity	Up to 128GB
Remote	IE Browser, CMS Software up to 4 simultaneous users
Protocol	TCP/IP,UDP,DHCP,NTP,RTSP,PPPoE,DDNS,SMTP,FTP
Housing Rating	IP67
Power Supply	DC 12V / PoE
Power Usage	<6W with IR on
Operating Env.	-30°~ 50°C, 10%~90% Humidity
Dimensions	Ø 87 x 95mm
Weight	500g

Product specifications and appearance subject to change without notice

**H.265  
HEVC**


More **efficient** video encoding allows for **longer** recording time without sacrificing image **quality**

**128GB  
SD Card  
Recording**



## Mounting Accessories

JB-EB



WM-EB



WM-EX

