

MYX

IPD5-28F

5MP PoE IP Dome

Features

- 5MP (2592×1944) H.265 full real-time encoding
- Intelligence Analytics smart triggering
- ICR auto switch, true day / night
- 10 ~ 20m IR night view distance
- 3D DNR, digital WDR
- ROI encoding
- Support CVBS video output and one-way audio
- Support PoE power supply
- Support smart phone, iPad, remote monitoring
- Triple Stream
- IP66 ingress protection



Intelligence Analytics

Get **FAST** search results by configuring in-built **image analytic algorithms**.

Supports Tripwire, Abandoned Object, Missing Object, Video Exception & Intrusion



Specifications




Image Sensor	1/1.8" CMOS
Resolution	5MP(2592x1944), 4MP, 2MP, 720P, D1, CIF
Min. Illumination	0.05 lux @F1.2, AGC on; 0 lux with IR
Lens	2.8mm @F1.6, Angle of View 95°
Day & Night	ICR Filter
Video Format	H.265 / H264 / MJPEG
Main Stream	60Hz: 5MP/4MP/3MP/2MP/720P(1~30fps) 50Hz: 5MP/4MP/3MP/2MP/720P(1~25fps)
Wide Dynamic	Digital WDR
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, Noise Reduction
Audio	Mic input x1
Video Out	CVBS
Smart Alarm	Motion Alarm, Intelligence Analytics
IR Distance	10~20m
Remote	IE Browser, CMS Software up to 4 simultaneous users
Protocol	TCP/IP,UDP,DHCP,NTP,RTSP,PPPoE,DDNS,SMTP,FTP
Housing Rating	IP66
Power Supply	DC 12V / 48V PoE
Power Usage	<3.5W (<5W with IR on)
Operating Env.	-20°~ 50°C, 10%~90% Humidity
Dimensions	Ø 87 x 108mm
Weight	427g

Product specifications and appearance subject to change without notice

H.265 HEVC

More **efficient** video encoding allows for **longer** recording time without sacrificing image **quality**

Mounting Accessories



5MP Sensor	0 Lux Min. Illumination	Digital WDR	Motion Detection	True Day&Night
AWB	Sync	AGC	PoE	IP66 Rating



www.cctvsupplies.com.au

2/175 Currumburra Road
Ashmore, Qld 4212
(07) 5527 9949