

MYX

IPD5-3312ME

5MP PoE IP Dome

Features

- 5MP (2592×1944) H.265 full real time encoding
- 3.3-12mm Motorized Auto-Focus Lens
- Intelligence Analytics smart triggering
- ICR auto switch, true day / night
- 20 ~ 30m IR night view distance
- 3D DNR, digital WDR
- ROI encoding
- Support CVBS video output and one-way audio
- Support PoE power supply
- Support smart phone, iPad, remote monitoring
- IP66 ingress protection
- Triple Stream



AUTOFOCUS

ONVIF

Intelligence Analytics

Get **FAST** search results by configuring in-built **image analytic algorithms**.

Supports Tripwire, Abandoned Object, Missing Object, Video Exception & Intrusion



Specifications

Image Sensor	1/2.5" CMOS
Resolution	5MP(2592×1944), 4MP, 2MP, 720P, D1, CIF
Min. Illumination	0.05 lux @F1.2, AGC on; 0 lux with IR
Lens	3.3~12mm Motorized Vari-focal @F1.4, AoV 94°~35°
Day & Night	ICR Filter
Video Format	H.265 / H264 / MJPEG
Main Stream	60Hz: 5MP/4MP/3MP/2MP/720P(1~30fps) 50Hz: 5MP/4MP/3MP/2MP/720P(1~25fps)
Wide Dynamic	Digital WDR
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, Noise Reduction
Audio	Mic input x1
Video Out	CVBS
Smart Alarm	Motion Alarm, Intelligence Analytics
IR Distance	20~30m
Remote	IE Browser, CMS Software up to 4 simultaneous users
Protocol	TCP/IP,UDP,DHCP,NTP,RTSP,PPPoE,DDNS,SMTP,FTP
Housing Rating	IP66
Power Supply	DC 12V / 48V PoE
Power Usage	<2.5W (<6W with IR on)
Operating Env.	-20°~ 50°C, 10%~90% Humidity
Dimensions	Ø 130mm x (H)109mm
Weight	697g

Product specifications and appearance subject to change without notice

H.265 HEVC

More **efficient** video encoding allows for **longer** recording time without sacrificing image **quality**

5MP Sensor	0 Lux Min. Illumination	Digital WDR	Motion Detection	True Day&Night
AWB	Sync	AGC	PoE	IP66 Rating

Mounting Accessories



www.cctvsupplies.com.au

2/175 Currumburra Road
Ashmore, Qld 4212
(07) 5527 9949