

MYX 3MP IP PTZ

IPZ20H

Features:

- 1/2.8" CMOS progressive scan, 20x optical zoom
- HD network video output: 2048x1536 (3MP) @25/30fps
- H.265 image compression format
- SD card local storage, network remote storage
- Web GUI Menu
- Support selected area PTZ function
- IP66 ingress protection: TVS 6KV lightning protection, surge protection
- 100m IR night view distance



ONVIF

100M IR  20x Optical Zoom

H.265 HEVC More efficient video encoding allows for longer recording time without sacrificing image quality

128GB SD Card Recording 


1/2.8"
CMOS Sensor


TVL 1200
1200TVL


Min. illumination


BLC


Day&Night


Auto WB


IP66


Web GUI

Specifications:

Image sensor	1/2.8" Progressive CMOS
Resolution	2048x1536 3-Megapixel, 1080P, 720P
Min.illumination	0 Lux with IP on
IR Distance	100m
White balance	Auto/Manual
Focus mode	Auto/Manual
Lens	20x zoom, f=5.5 ~ 110mm, F1.6~F3.5
Compression	H.265
Frame rate	1~30fps(25fps)
Pan range	360° endless rotation
Pan speed	Preset speed: 240°/s; Manual speed: 0.5~90°/s
Tilt range	0~93°(auto rotation)
Tilt speed	Preset speed: 160°/s; Manual speed: 0.5~90°/s
Preset	255
Cruise	8
Track	4
Time task	8
Scan	2
Home position	Yes
Auto flip	Yes
Alarm in/out	1/1
Alarm linkage	Yes
Video output	AHD/TVI selectable
Audio	MIC input x 1, MIC output x 1
Protocol	TCP/IP,UDP,DHCP,DDNS,NTP,RTSP,SMTP,FTP,PPPoE
Storage	SD card local storage, network remote storage
Smart alarm	Motion alarm, Sensor alarm
Multi-stream	Yes
Network interface	10 base-T / 100 base-TX / RS-485
Power supply	24VAC 3A included
Power usage	15W(max 30W, IR on)
Working Env.	Temperature: -20°~ 60°; humidity: less than 95%
Protection level	IP66; TVS 6KV lightning protection, surge protection
Dimension(mm)	Φ209mm × 317mm
Weight	3.5KG

Product specifications and appearance subject to change without notice



www.cctvsupplies.com.au

2/175 Currumburra Road
Ashmore, Qld 4212
(07) 5527 9949